

ICS Bond-1400

Anti-Strip Agent



International
Chemical
Group

Description:

ICS Bond-1400 is anti-stripping agent based on a modified Polyamine.

Applications:

ICS Bond-1400 is used as an anti-stripping agent for both hot-mix asphalt pavements and cold patch asphalt mixes.

ICS Bond-1400 is added directly into the asphalt by circulation, mechanical agitation or by continuous injection into the load line and subsequent re-circulation in the truck.

Dosage:

ICS Bond-1400 is used at a dosage from 0.5% to 1.0% for hot mix asphalt

For cold patch mixes, the dosage is 0.5% to 1.5%

Physical Properties

Appearance	Thick Yellow Liquid
Odour	Amine
Melting Point	15 C (59 °F)
Flash Point	> 230 C (> 446 °F)

Packaging:

ICS Bond-1400 is available in drum or tote quantities.

Handling:

Please refer to the Material Safety Data Sheet for further handling information.

Technical Data Sheet

Liability Disclaimer - The information in this Data Sheet is provided without suggestion of warranty or guarantee. "Physical Properties" are typically values rather than specifications. The user is responsible for investigation for suitability of this product for their own use.



International Chemical Service Ltd.
Suite 1378 – 5328 Calgary Trail NW
Edmonton, Alberta, Canada T6H 4J8
P: 780-433-4352 F: 780-669-3764
E: info@intlchemgroup.com



Integrated Chemical Services Inc.
4830 Wilson Rd, Ste 300 PMB 14
Houston, Texas, USA 77396
P: 866-433-4352 F: 780-669-3764
E: info@intlchemgroup.com