

ICS Emul-2470

Asphalt Emulsifier



International
Chemical
Group

Description:

ICS Emul-2470 is cationic polyamine emulsifier.

Applications:

ICS Emul-2470 is an emulsifier for both cationic and anionic slow set emulsions.

Slow set emulsions will include tack coat, prime coat, slurry seal, seal coat and cold mix asphalt.

ICS Emul-2470 is effective over a wide range of ratios of asphalt / bitumen to aggregate.

Dosage:

ICS Emul-2470 is used at a dosage of 2.0 % to 3.0% in the emulsion.

Physical Properties:

| | |
|------------|---------------|
| Appearance | Yellow liquid |
| Odour | Amine |
| Density | 1.07 @ 20 C |
| pH | 5-8 |
| Pour Point | - 7 C |

Packaging:

ICS Emul-2470 is available in drum or tote quantities.

Handling:

Please refer to the Material Safety Data Sheet for further handling information.

Technical Data Sheet

Liability Disclaimer - The information in this Data Sheet is provided without suggestion of warranty or guarantee. "Physical Properties" are typically values rather than specifications. The user is responsible for investigation for suitability of this product for their own use.



International Chemical Service Ltd.
Suite 1378 – 5328 Calgary Trail NW
Edmonton, Alberta, Canada T6H 4J8
P: 780-433-4352 F: 780-669-3764
E: info@intlchemgroup.com



Integrated Chemical Services Inc.
4830 Wilson Rd, Ste 300 PMB 14
Houston, Texas, USA 77396
P: 866-433-4352 F: 780-669-3764
E: info@intlchemgroup.com